



全钢载重子午线轮胎技术参数

ALL STEEL HEAVY RADIAL TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮辋 STANDA RD RIM | 负荷指数 LOAD INDEX | 充气压力 (kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH(mm) | 外直径 (mm) EXAME TE(mm) |
|-------------|------------------|----------------------------|------------------------------|--------------------|---|--------------------------------|------------|-------------------------------------|--------------------------------|
| | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 8.25R16LT | 14 | M | 6.50H | 126/122 | 670 | 1700 | 1500 | 235 | 856 |
| 8.25R16LT | 16 | M | 6.50H | 128/124 | 770 | 1800 | 1600 | 235 | 856 |
| 7.50R20 | 14 | L | 6.0 | 130/126 | 770 | 1885 | 1700 | 215 | 935 |
| 8.25R20 | 14 | L | 6.5 | 136/131 | 840/770 | 2240 | 1950 | 232 | 971 |
| 8.25R20 | 16 | L | 6.5 | 139/137 | 930 | 2430 | 2300 | 232 | 971 |
| 9.00R20 | 14 | L | 7.0 | 141/139 | 790 | 2575 | 2430 | 258 | 1022 |
| 9.00R20 | 16 | L | 7.0 | 144/142 | 900 | 2800 | 2650 | 258 | 1022 |
| 10.00R20 | 16 | L | 7.5 | 146/143 | 830 | 3000 | 2725 | 273 | 1053 |
| 10.00R20 | 18 | L | 7.5 | 149/146 | 930 | 3250 | 3000 | 273 | 1053 |
| 11.00R20 | 16 | L | 8.0 | 150/147 | 830 | 3350 | 3075 | 287 | 1087 |
| 11.00R20 | 18 | L | 8.0 | 152/149 | 930 | 3550 | 3250 | 287 | 1087 |
| 12.00R20 | 18 | L | 8.5 | 154/151 | 830 | 3750 | 3450 | 310 | 1122 |
| 12.00R20 | 20 | L | 8.5 | 156/153 | 900 | 4000 | 3650 | 310 | 1122 |
| 12.00R24 | 18 | K | 8.5 | 156/153 | 830 | 4000 | 3650 | 313 | 1226 |
| 11R22.5 | 14 | M | 8.25 | 144/142 | 720 | 2800 | 2650 | 279 | 1050 |
| 11R22.5 | 16 | M | 8.25 | 146/143 | 830 | 3000 | 2725 | 279 | 1050 |
| 11R24.5 | 14 | M | 8.25 | 146/143 | 720 | 3000 | 2725 | 279 | 1103 |
| 11R24.5 | 16 | L | 8.25 | 149/146 | 830 | 3250 | 3000 | 279 | 1103 |
| 275/80R22.5 | 16 | M | 8.25 | 148/144 | 840 | 3150 | 2800 | 277 | 1020 |
| 295/80R22.5 | 16 | M | 9.00 | 152/148 | 840 | 3550 | 3150 | 298 | 1041 |
| 315/80R22.5 | 16 | M | 9.00 | 151/148 | 760 | 3450 | 3150 | 314 | 1075 |
| 315/80R22.5 | 18 | M | 9.00 | 154/151 | 830 | 3750 | 3450 | 314 | 1075 |
| 285/75R24.5 | 14 | M | 8.25 | 144/141 | 760 | 2800 | 2575 | 283 | 1050 |
| 285/75R24.5 | 16 | L | 8.25 | 147/144 | 830 | 3075 | 2800 | 283 | 1050 |
| 295/75R22.5 | 14 | M | 9.00 | 144/141 | 760 | 2800 | 2575 | 298 | 1010 |
| 295/75R22.5 | 16 | L | 9.00 | 146/143 | 830 | 3000 | 2725 | 298 | 1010 |
| 255/70R22.5 | 16 | L | 7.50 | 140/137 | 840 | 2500 | 2300 | 253 | 926 |
| 385/65R22.5 | 18 | L | 11.75 | 158 | 840 | 4250 | -- | 390 | 1066 |

全钢工程子午线轮胎技术参数

ALL STEEL ENGINEERING RADIAL TYRE SPECIFICATION

| 轮胎规格 Tyre size | 强度 Intensity | 负荷指数 Load in | 花纹编号 Patten NO. | 标准轮辋 Standard rim | 外直径 Diameter | 断面宽 Section Width | 最大负荷 Allowable load | 标准气压 (bar) Standard barometric | 最高时速 (km/h) Top speed per hour |
|-------------------|-----------------|-----------------|--------------------|----------------------|-----------------|-------------------------|------------------------|---|---|
| 17.5R25TL | ★ | 182/167 | XB01N | 14.00/1.5 | 1348 | 445 | 8500/5450 | 5.75/4.5 | 10/50 |
| | ★★ | 176/153/157 | | | | | 7100/3650/4125 | 4.5/3.0/3.5 | 10/40/50 |
| 20.5R25TL | ★ | 193/177 | XB01N | 17.00/2.0 | 1492 | 520 | 11500/7300 | 5.75/4.5 | 10/50 |
| | ★★ | 186/161/168 | | | | | 9500/4625/5600 | 4.5/3.75/3.5 | 10/40/50 |
| 23.5R25TL | ★ | 201/185 | XB01N | 19.50/2.5 | 1617 | 597 | 14500/9250 | 6.5/5.25 | 10/50 |
| | ★★ | 195/176 | | | | | 12150/7100 | 5.0/3.75 | |
| 26.5R25TL | ★ | 209/193 | XB01N | 22.00/3.0 | 1750 | 673 | 18500/11500 | 5.75/4.5 | 10/50 |
| | ★★ | 202/184 | | | | | 15000/9000 | 4.5/3.5 | |
| 29.5R25TL | ★ | 216/200 | XB02N | 25.00/3.5 | 1873 | 750 | 22400/14000 | 5.75/4.5 | 10/50 |
| | ★★ | 208/191 | | | | | 18000/10900 | 4.5/3.5 | |



300

花纹特点: PATTERN CHARACTERISTIC

混合顺向花纹, 优异的抓着性能, 防侧滑, 变节距设计, 低行驶噪音, 适合城乡各种路面使用。

Mixed rib pattern; Good ground grasping capability; Sideslip resistance; Pitch pattern designed; Low noise; Suitable for all kinds of the roads of the town;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAMETER |
|------------|------------------|----------------------------|------------------------------|----------------------------------|-------------------|---|--------------------------------|------------|---------------------------------|-------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 7.50R20 | 14 | L | 6.0 | 6.00T, 6.5, 6.50T | 130/126 | 770 | 1885 | 1700 | 215 | 935 |
| 8.25R16LT | 14 | M | 6.50H | 6.00G | 126/122 | 670 | 1700 | 1500 | 235 | 856 |
| 8.25R16LT | 16 | M | | | 128/124 | 770 | 1800 | 1600 | | |
| 8.25R20 | 14 | L | | | 6.5 | 6.50T, 7.0 | 136/131 | 840-770 | 2240 | 1950 |
| 8.25R20 | 16 | L | 139/137 | 930 | | | 2430 | 2300 | | |
| 9.00R20 | 14 | L | 7.0 | 7.00T, 7.0T5* , 7.5 , 7.50 V | 141/139 | 790 | 2575 | 2430 | 258 | 1022 |
| 9.00R20 | 16 | L | 7.5 | 7.50V, 8.0, 8.00V , 8.0 V5* | 146/143 | 830 | 3000 | 2725 | | |
| 10.00R20 | 16 | L | 8.0 | 8.00V, 8.5, 8.5, 50V, 8.5 V5* | 149/146 | 930 | 3250 | 3000 | 273 | 1053 |
| 10.00R20 | 18 | L | | | 150/147 | 830 | 3350 | 3075 | | |
| 11.00R20 | 16 | L | 8.5 | 8.50V, 8.5 V5* + , 9.00V | 152/149 | 930 | 3550 | 3250 | 287 | 1087 |
| 11.00R20 | 18 | L | | | 154/151 | 830 | 3750 | 3450 | | |
| 12.00R20 | 20 | L | 8.5 | 8.50V, 8.5 V5* + , 9.00V | 156/153 | 900 | 4000 | 3650 | 310 | 1122 |
| 12.00R24 | 18 | K | | | 156/153 | 830 | 4000 | 3650 | | |



301

花纹特点: PATTERN CHARACTERISTIC

高性能混合花纹, 半独立冠部花纹, 一体化肩部花纹, 高负荷能力, 适合各种复杂路面使用。

High powered mixed pattern; Quasi-sovereign tread pattern; Integrative shoulder pattern; High loading capability; Suitable for all kinds of the roads;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAMETER |
|------------|------------------|----------------------------|------------------------------|-----------------------------------|-------------------|---|--------------------------------|------------|---------------------------------|-------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 11.00R20 | 16 | L | 8.0 | 8.00V , 8.5, 8.50V, 8.5 V5* | 150/147 | 830 | 3350 | 3075 | 287 | 1087 |
| 11.00R20 | 18 | L | | | 152/149 | 930 | 3550 | 3250 | | |



302

花纹特点: PATTERN CHARACTERISTIC

超强的地面附着性能, 牵引、制动性能, 既不损失强载能力, 又保持高的性能, 定位为驱动轮。

Super ground grasping capability; Good traction and braking performance; Both have high loading and high speed capability; Designed for driving;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAMETER |
|------------|------------------|----------------------------|------------------------------|--------------------------------|-------------------|---|--------------------------------|------------|---------------------------------|-------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 10.00R20 | 16 | L | 7.5 | 7.50V , 8.0, 8.00V, 8.0 V5* | 146/143 | 830 | 3000 | 2725 | 273 | 1053 |
| 10.00R20 | 18 | L | | | 149/146 | 930 | 3250 | 3000 | | |
| 11.00R20 | 16 | L | 8.0 | 8.00V , 8.5, 8.50V, 8.5V5* | 150/147 | 830 | 3350 | 3075 | 287 | 1087 |
| 11.00R20 | 18 | L | | | 152/149 | 930 | 3550 | 3250 | | |



303

花纹特点: PATTERN CHARACTERISTIC

高速顺向花纹, 优异的高速性能, 持久耐磨, 降低路面冲击力, 适合优良路面使用。

Rib pattern; Super high speed capability; Good abrasion resistance; Reduce the wallop to the road; Suitable for good road tread;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAMETER |
|------------|------------------|----------------------------|------------------------------|--------------------------|-------------------|---|--------------------------------|------------|---------------------------------|-------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 12.00R24 | 18 | K | 8.5 | 8.50V, 8.5V5* , 9.00V | 156/153 | 830 | 4000 | 3650 | 313 | 1226 |



306

花纹特点: PATTERN CHARACTERISTIC

优异的牵引和越野性能,超强的地面附着性能,耐磨性能,有强载能力和胎面抗刺扎性能。

Good traction and off-roadness performance;Good ground grasping capability and abrasion resistance;High loading;Good puncture resistance;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAMETER |
|------------|------------------|----------------------------|------------------------------|-----------------------|-------------------|---|--------------------------------|------------|---------------------------------|-------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 10.00R20 | 16 | L | 7.5 | 7.50V,8.0, | 146/143 | 830 | 3000 | 2725 | 273 | 1053 |
| 10.00R20 | 18 | L | | 8.00V,8.0 V5° | 149/146 | | 930 | 3250 | | |
| 11.00R20 | 16 | L | 8.0 | 8.00V,8.5, | 150/147 | 830 | 3350 | 3075 | 287 | 1087 |
| 11.00R20 | 18 | L | | 8.50V, 8.5 V5° | 152/149 | | 930 | 3550 | | |
| 12.00R20 | 18 | L | 8.5 | 8.50V, 8.5 V5° | 154/151 | 830 | 3750 | 3450 | 310 | 1122 |
| 12.00R20 | 20 | L | | 9.00V | 156/153 | | 900 | 4000 | | |



308

花纹特点: PATTERN CHARACTERISTIC

耐磨性能好,载荷量高,耐刺扎,抓着力强,既适于较差路面,又适于较好路面。

Good abrasion and puncture resistance;Good loading capability;Good grasping performance;Suitable for rough road and high way;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAMETER |
|------------|------------------|----------------------------|------------------------------|------------------------------|-------------------|---|--------------------------------|------------|---------------------------------|-------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 10.00R20 | 16 | K | 7.5 | 7.50V ,8.0, 8.00V, 8.0V5° | 146/143 | 830 | 3000 | 2725 | 273 | 1058 |
| | 18 | K | | | 149/146 | | 930 | 3250 | | |



309

花纹特点: PATTERN CHARACTERISTIC

强力混合花纹,提供强劲动力,超深花纹设计,高行驶寿命,耐磨,抗刺扎,适用于矿山、山地路面使用。

Super mixed pattern;Super traction ability;Additional tread depth;Long using life;Good abrasion and puncture resistance;Suitable for coalmine and mountainous region;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAMETER |
|------------|------------------|----------------------------|------------------------------|-----------------------|-------------------|---|--------------------------------|------------|---------------------------------|-------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 10.00R20 | 16 | J | 7.5 | 7.50V,8.0, | 146/143 | 830 | 3000 | 2725 | 273 | 1053 |
| 10.00R20 | 18 | J | | 8.00V,8.0 V5° | 149/146 | | 930 | 3250 | | |
| 11.00R20 | 16 | J | 8.0 | 8.00V,8.5, | 150/147 | 830 | 3350 | 3075 | 287 | 1087 |
| 11.00R20 | 18 | J | | 8.50V, 8.5 V5° | 152/149 | | 930 | 3550 | | |
| 12.00R20 | 18 | J | 8.5 | 8.50V, 8.5 V5° | 154/151 | 830 | 3750 | 3450 | 310 | 1122 |
| 12.00R20 | 20 | J | | 9.00V | 156/153 | | 900 | 4000 | | |



100

花纹特点: PATTERN CHARACTERISTIC

高速顺向花纹,变节距设计,低行驶噪音,低滚动阻力,持久耐磨,抗侧滑性能,适合高速行驶。

High speed rib pattern;Pitch pattern designed;Low noise;Low rolling resistance;Good abrasion resistance and sideslip resistance;Suitable for high way;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAMETER |
|-------------|------------------|----------------------------|------------------------------|-----------------------|-------------------|---|--------------------------------|------------|---------------------------------|-------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 7.50R20 | 14 | L | 6.0 | 6.00T,6.5,6.50T | 130/126 | 770 | 1885 | 1700 | 215 | 935 |
| 9.00R20 | 14 | L | 7.0 | 7.00T,7.0T5° | 141/139 | 790 | 2575 | 2430 | 258 | 1022 |
| 9.00R20 | 16 | L | | 7.5, 7.50V | 144/142 | 900 | 2800 | 2650 | | |
| 10.00R20 | 16 | L | 7.5 | 7.50V,8.0, | 146/143 | 830 | 3000 | 2725 | 273 | 1053 |
| 10.00R20 | 18 | L | | 8.00V, 8.0V5° | 149/146 | | 930 | 3250 | | |
| 11.00R20 | 16 | L | 8.0 | 8.00V, 8.5,8, | 150/147 | 830 | 3350 | 3075 | 287 | 1087 |
| 11.00R20 | 18 | L | | 8.50V, 8.5V5° | 152/149 | | 930 | 3550 | | |
| 12.00R20 | 18 | L | 8.5 | 8.50V, 8.5V5° | 154/151 | 830 | 3750 | 3450 | 310 | 1122 |
| 12.00R20 | 20 | L | | 9.00V | 156/153 | | 900 | 4000 | | |
| 11R22.5 | 14 | M | 8.25 | 7.50 | 144/142 | 720 | 2800 | 2650 | 279 | 1050 |
| 11R22.5 | 16 | M | | | 146/143 | 830 | 3000 | 2725 | | |
| 315/80R22.5 | 16 | M | 9.00 | — | 151/148 | 760 | 3450 | 3150 | 314 | 1075 |
| 315/80R22.5 | 18 | M | | | 154/151 | 830 | 3750 | 3450 | | |

载重子午线轮胎



200

花纹特点: PATTERN CHARACTERISTIC

超强的地面附着性能, 抗湿滑性能优异, 行驶震动小, 既适于较差路面, 又适于高速公路。

Good ground grasping capability and sideslip resistance; Low shock when running; Both suitable for rough road and high way surface;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAME TER |
|------------|------------------|----------------------------|------------------------------|-------------------------|-------------------|---|--------------------------------|------------|---------------------------------|--------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 8.25R16LT | 14 | M | 6.50H | 6.00G | 126/122 | 670 | 1700 | 1500 | 235 | 856 |
| 8.25R16LT | 16 | M | | | 128/124 | | 1800 | 1600 | | |
| 8.25R20 | 14 | L | 6.5 | 6.50T,7.0 | 136/131 | 840/770 | 2240 | 1950 | 232 | 971 |
| 8.25R20 | 16 | L | 6.5 | 6.50T,7.0 | 139/137 | 930 | 2430 | 2300 | 232 | 971 |
| 12.00R24 | 18 | K | 8.5 | 8.00V, 8.5V5', 9.00V | 156/153 | 830 | 4000 | 3650 | 313 | 1226 |



201

花纹特点: PATTERN CHARACTERISTIC

优异的牵引、制动性能, 耐磨, 载重量高, 长行驶寿命。

Good traction and braking performance; Good abrasion resistance; High loading capability; Long using life;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAME TER |
|------------|------------------|----------------------------|------------------------------|---------------------------|-------------------|---|--------------------------------|------------|---------------------------------|--------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 8.25R16LT | 14 | M | 6.50H | 6.00G | 126/122 | 670 | 1700 | 1500 | 235 | 856 |
| 8.25R16LT | 16 | M | | | 128/124 | | 1800 | 1600 | | |
| 8.25R20 | 14 | L | 6.5 | 6.50T,7.0 7.00T,7.0T5* | 136/131 | 840/770 | 2240 | 1950 | 232 | 971 |
| 8.25R20 | 16 | L | 6.5 | 6.50T,7.0 | 139/137 | 930 | 2430 | 2300 | 232 | 971 |



600

花纹特点: PATTERN CHARACTERISTIC

卓越的防不规则磨蚀性能, 较高的行驶里程, 行驶噪音低, 适于高速行驶。

Avoiding anomalous abrasion; Longer mileage; Low noise; Suitable for high way speed;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAME TER |
|-------------|------------------|----------------------------|------------------------------|-----------------------|-------------------|---|--------------------------------|------------|---------------------------------|--------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 11R22.5 | 14 | M | 8.25 | 7.50 | 144/142 | 720 | 2800 | 2650 | 279 | 1050 |
| 11R22.5 | 16 | M | | | 146/143 | | 830 | 3000 | | |
| 11R24.5 | 14 | M | 8.25 | 7.50 | 146/143 | 720 | 3000 | 2725 | 279 | 1103 |
| 11R24.5 | 16 | L | | | 149/146 | | 830 | 3250 | | |
| 285/75R24.5 | 14 | M | 8.25 | 8.25 | 144/141 | 760 | 2800 | 2575 | 283 | 1050 |
| 285/75R24.5 | 16 | L | | | 147/144 | | 830 | 3075 | | |
| 295/75R22.5 | 14 | M | 9.00 | 8.25,9.00 | 144/141 | 760 | 2800 | 2575 | 298 | 1010 |
| 295/75R22.5 | 16 | L | | | 146/143 | | 830 | 3000 | | |



660

花纹特点: PATTERN CHARACTERISTIC

在雪地, 泥泞路面均具有较强的地面附着性能, 优异的牵引、耐磨性能, 行驶噪音低, 有较高的行驶里程。

Good ground grasping capability on snow and miry road; Good traction performance; Good abrasion resistance; Low noise when running; Longer mileage;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮胎 STANDA RD RIM | 许用轮胎 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAME TER |
|-------------|------------------|----------------------------|------------------------------|-----------------------|-------------------|---|--------------------------------|------------|---------------------------------|--------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 11R22.5 | 14 | M | 8.25 | 7.50 | 144/142 | 720 | 2800 | 2650 | 279 | 1050 |
| 11R22.5 | 16 | M | | | 146/143 | | 830 | 3000 | | |
| 11R24.5 | 14 | M | 8.25 | 7.50 | 146/143 | 720 | 3000 | 2725 | 279 | 1103 |
| 11R24.5 | 16 | L | | | 149/146 | | 830 | 3250 | | |
| 285/75R24.5 | 14 | M | 8.25 | 8.25 | 144/141 | 760 | 2800 | 2575 | 283 | 1050 |
| 285/75R24.5 | 16 | L | | | 147/144 | | 830 | 3075 | | |
| 295/75R22.5 | 14 | M | 9.00 | 8.25,9.00 | 144/141 | 760 | 2800 | 2575 | 298 | 1010 |
| 295/75R22.5 | 16 | L | | | 146/143 | | 830 | 3000 | | |

载重子午线轮胎

ALL STEEL HEAVY RADIAL TYRE SERIES



766

花纹特点: PATTERN CHARACTERISTIC

高速、高载、超强的抗侧滑、湿滑性能,适用于前轮位、全轮位。

High speed;High loading capability;Good sideslip and mud slip resistance;Suitable for guiding and all use;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮辋 STANDA RD RIM | 许用轮辋 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAME TER |
|-------------|------------------|----------------------------|------------------------------|-----------------------|-------------------|---|--------------------------------|------------|---------------------------------|--------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 12R22.5 | 18 | M | 9.00 | 8.25 | 152/148 | 850 | 3550 | 3150 | 300 | 1084 |
| 295/80R22.5 | 16 | M | 9.00 | 8.25 | 152/148 | 850 | 3550 | 3150 | 298 | 1044 |
| 315/80R22.5 | 16 | M | 9.00 | 9.75 | 151/148 | 760 | 3450 | 3150 | 314 | 1075 |
| | 18 | M | | | 154/151 | 830 | 3750 | 3450 | | |



755

花纹特点: PATTERN CHARACTERISTIC

高速、高载,优异的牵引、制动、附着性能,适用于驱动轮位。

High speed;High loading capability;Good traction, braking and ground grasping capability;Suitable for driving;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮辋 STANDA RD RIM | 许用轮辋 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAME TER |
|-------------|------------------|----------------------------|------------------------------|-----------------------|-------------------|---|--------------------------------|------------|---------------------------------|--------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 11.00R22 | 18 | L | 8.00 | 8.00V,8.5 | 154/151 | 930 | 3750 | 3450 | 293 | 1135 |
| 12R22.5 | 18 | M | 9.00 | 8.25 | 152/148 | 850 | 3550 | 3150 | 300 | 1084 |
| 295/60R22.5 | 16 | M | 9.00 | 9.75 | 149/146 | 900 | 3450 | 3000 | 292 | 926 |
| 315/60R22.5 | 16 | M | 9.75 | 9.75 | 152/148 | 900 | 3550 | 3150 | 313 | 950 |
| 305/70R22.5 | 16 | M | 9.00 | 8.25 | 152/148 | 900 | 3550 | 3150 | 305 | 1000 |
| 315/70R22.5 | 16 | M | 9.00 | 9.75 | 154/150 | 900 | 3750 | 3350 | 312 | 1014 |
| 295/80R22.5 | 16 | M | 9.00 | 8.25 | 152/148 | 850 | 3550 | 3150 | 298 | 1044 |
| 315/80R22.5 | 16 | M | 9.00 | 9.75 | 151/148 | 760 | 3450 | 3150 | 314 | 1075 |
| | 18 | M | | | 154/151 | 830 | 3750 | 3450 | | |



880

花纹特点: PATTERN CHARACTERISTIC

轮胎使用寿命长,具有优异的牵引性能,适用于高速公路客车、卡车的驱动轮位。

Long using life;Good traction capability;Suitable for all use of the bus and the driving tyre of the truck;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮辋 STANDA RD RIM | 许用轮辋 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAME TER |
|-------------|------------------|----------------------------|------------------------------|-----------------------|-------------------|---|--------------------------------|------------|---------------------------------|--------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 11R22.5 | 14 | M | 8.25 | 7.50 | 144/142 | 720 | 2800 | 2650 | 279 | 1050 |
| 11R22.5 | 16 | M | | | 146/143 | 830 | 3000 | 2725 | | |
| 11R24.5 | 14 | M | 8.25 | 7.50 | 146/143 | 720 | 3000 | 2725 | 279 | 1103 |
| 11R24.5 | 16 | L | | | 149/146 | 830 | 3250 | 3000 | | |
| 285/75R24.5 | 14 | M | 8.25 | 8.25 | 144/141 | 760 | 2800 | 2575 | 283 | 1050 |
| 285/75R24.5 | 16 | L | | | 147/144 | 830 | 3075 | 2800 | | |
| 295/75R22.5 | 14 | M | 9.00 | 8.25,9.00 | 144/141 | 760 | 2800 | 2575 | 298 | 1010 |
| 295/75R22.5 | 16 | L | | | 146/143 | 830 | 3000 | 2725 | | |



990

花纹特点: PATTERN CHARACTERISTIC

优异的牵引性能,高速行驶情况下轮胎使用寿命长,适用于客车、卡车的驱动轮位。

Good traction capability;Long using life under high speed situation;Suitable for bus and truck;

技术参数 TYRE SPECIFICATION

| 规格 SIZE | 层级 PLY-RATING | 速度 级别 SPEED RANGE | 标准 轮辋 STANDA RD RIM | 许用轮辋 ALLOWABLE RIM | 负荷指数 LOADINDEX | 充气压力(kPa) INFLATION PRESSURE(kPa) | 负荷能力 (kg) LOAD CAPACITY(kg) | | 断面宽 (mm) SECTION WIDTH | 外直径 (mm) DIAME TER |
|-------------|------------------|----------------------------|------------------------------|-----------------------|-------------------|---|--------------------------------|------------|---------------------------------|--------------------------|
| | | | | | | | 单胎 SINGLE | 双胎 DUAL | | |
| 385/65R22.5 | 18 | L | 11.75 | 12.25 | 158 | 830 | 4250 | 389 | 1072 | |
| | 20 | K | | | 160 | 900 | 4500 | | | |
| 425/65R22.5 | 18 | L | 14.00 | 14.00 | 162 | 830 | 4750 | 430 | 1124 | |
| | 20 | K | | | 165 | 900 | 5150 | | | |